


SPECIFICATIONS	837/30	882/30
	836.5 NOM	
	30 NOM	
	824-849	
	3.5 dB	
	795,869-894	724-849,940
PASSBAND RIPPLE	≤ 1.0	1.0
VSWR	≤ 1.7:1	≤ 1.7:1
IMPEDANCE(OHMS)	50	50

COPY

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.



NOTES:
 1) DC: IS ON ONE SIDE ONLY.
 2) THERE MUST BE A MINIMUM OF .05'

ENGLISH / METRIC ENGLISH	CHECKED BY	B	24JUL01	MJG	DEV.	GEN. REV. PER 1678
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125 OR BETTER REMOVE ALL BURRS	DRAWN BY	A	11MAR99	MJG	DEV.	GEN. REV. PER 0965
	ENGINEER	II	21NOV96	MJG	DEV.	INI. ISS. PER 0123
	MJG	REV	DATE	BY	DCN No.	REMARKS
ENGLISH (INCHES) .XX ±.01 .XXX ±.005	SCALE	APPLIC: CERAMIC COAXIAL FILTER				
METRIC (MM) .X ±.25 .XX ±.13	2:1					
ANGLES ± 0° 30'	DATE	TITLE: 11DCR6E-837/882/C30-D				SHEET NO/OF 1 1
	25JUL01					
	FINISH:	JACKET: NI/SIL RES.: SILVER PINS: TIN PLATED BRASS				DRAWING No. 0L0010