


RECOMMENDED FOOT PRINT

COPY

Electrical Specifications	1760/45	1850/45
Center Frequency (MHz):	1760 nom.	1850 nom.
Passband (MHz):	1750 - 1780	1840 - 1870
Passband loss:	< 2.5 dB	< 2.5 dB
Passband VSWR:	1.7:1	1.7:1
35 dB rejection (MHz):	DC - 1710	1910 - 4500
48 dB rejection (MHz):	1840 - 4500	DC - 1780
Impedance:	50 ohms	50 ohms
Temperature range:	-40 to +85° C	-40 to +85° C

 TIN PLATED COPPER ON BOTTOM OF BOARD
 TIN PLATED COPPER ON TOP OF BOARD

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the creation, last revision, and last updated dates. All Rights Reserved.



NOTES:
 DRAWING NOT TO SCALE
 MAX REFLOW TEMP. 240°C FOR 30 SEC.,
 OR 260°C FOR 15 SEC.
 NOTE1 AS REQUIRED FOR 50 OHMS
 CONNECTING LINE ON BOARD
 BACK-PLANE

ENGLISH / METRIC ENGLISH	CHECKED BY				
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125 / OR BETTER REMOVE ALL BURRS	DRAWN BY PBF				
ENGLISH (INCHES) .XX ±.01 .XXX ±.005	ENGINEER MJG	II	20JAN9	MJG	DEV.
METRIC (MM) .X ±.25 .XX ±.13	SCALE N/A	REV	DATE	BY	DCN No.
ANGLES ± 0° 30'	DATE 20JAN99	APPLIC: COAXIAL FILTER			INT. ISS. PER 0908
COMNAV ENGINEERING INC.	MATERIAL: N/A	TITLE: 9DCR6B-1760/1850/45-D			SHEET NO/OF 1 1
	FINISH: N/A	DRAWING No. OL0160			