



Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

NOTES:

HAND OR WAVE SOLDERING.  
 MAX REFLOW TEMP. 240°C FOR 30 SEC.,  
 OR 260°C FOR 15 SEC.  
 NOTE 1 THERE MUST BE A MINIMUM OF .050  
 AIR BETWEEN GROUND AND HIGH IMPEDANCE  
 POINTS. THIS MAY BE DONE BY RAISING  
 THE FILTER OR BY DRILLING OUT THE BOARD.  
 FOOTPRINT AVAILABLE UPON REQUEST.

ENGLISH / METRIC ENGLISH		CHECKED BY							
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125 / OR BETTER REMOVE ALL BURRS		DRAWN BY	A	23JAN01	SWB	DEV.	GEN. REV. PER 1560		
		ENGINEER	II	09AUG99	SWB	DEV.	INI. ISS. PER 1067		
		SWB	REV	DATE	BY	DCN No.	REMARKS		
ENGLISH (INCHES) .XX ±.02 .XXX ±.010	METRIC (MM) .X ±.25 .XX ±.13	SCALE	APPLIC: CERAMIC COAXIAL FILTER						
ANGLES ± 0° 30'		DATE	30MAR01		TITLE: 11DCR12C-838/883/C30-D			SHEET NO/OF 1 1	
					FINISH: BOARD: TINPLATED COPPER JACKET: NI/SILVER RESONATOR: SILVER		DRAWING No. 0L0209		