



**NOTES:**

FOR RECOMMENDED FOOTPRINT SEE FP0025.

RECOMMENDED ATTACHMENT METHOD: SILVER EPOXY  
OR REFLOW NOT TO EXCEED AS INDICATED BELOW:

TEMP.(°C)	MAX.TIME(SEC)
215	90
230	60
245	30
260	15

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.						<span style="font-size: 1.5em; font-weight: bold;">A</span>
ENGLISH / METRIC ENGLISH	CHECKED BY					
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125/ OR BETTER REMOVE ALL BURRS	DRAWN BY PBF	A	19MAR04	MJG	DEV.	GEN. REV. PER 2205
	ENGINEER MJG	II	03OCT03	MJG	DEV.	INI. ISS. PER 2123
	REV	DATE	BY	DCN No.	REMARKS	
ENGLISH (INCHES) .XX ±.01 .XXX ±.005	METRIC (MM) .X ±.25 .XX ±.13	SCALE 4:1		APPLIC: COAXIAL FILTER		
ANGLES ± 0° 30'	DATE 19MAR04	TITLE: 4BCR3E-1210.5/130-L				
	FINISH: BOARD: NI/AU PLATED COPPER JACKET: NI/SILVER RESONATOR: SILVER	DRAWING No. OL0489		SHEET OF 1 1		