



NOTES:

RECOMMENDED ATTACHMENT METHOD:
SILVER EPOXY OR REFLOW NOT TO
EXCEED AS INDICATED BELOW:

TEMP.(°C) MAX.	TIME(SEC)
215	90
230	60
245	30
260	15

ELECTRICAL CHARACTERISTICS

CENTER FREQUENCY:	473 MHz
PASSBAND:	450-496 MHz
PASSBAND LOSS:	<3.0 dB
35 dBc REJECTION:	FO±280 MHz

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.									
ENGLISH / METRIC ENGLISH		CHECKED BY							
TOLERANCES UNLESS OTHERWISE SPECIFIED		DRAWN BY		A	24SEP04	MJG	DEV.	GEN. REV. PER 2291	
MACHINED SURFACES TO BE 125/ OR BETTER REMOVE ALL BURRS		ENGINEER		II	25AUG04	MJG	DEV.	INI. ISS. PER 2287	
		MJC		REV	DATE	BY	DCN No.	REMARKS	
ENGLISH (INCHES)		METRIC (MM)		SCALE		APPLIC: CERAMIC COAXIAL FILTER			
.XX ±.02 .XXX ±.010		.X ±.25 .XX ±.13		4:1		TITLE: 3BCR4E-473/55-L			
ANGLES ± 0° 30'		DATE		24SEP04		DRAWING No. 010560			
		FINISH: BOARD: NI/GOLD JACKET: NI/SILVER RESONATOR: SILVER				SHEET OF 1 1			