



ELECTRICAL CHARACTERISTICS

PASSBAND:.....DC TO 375 MHz
 INSERTION LOSS:
 1.0 dB MAX @ DC TO 337.5 MHz
 AMPLITUDE RIPPLE:
 0.2 dB PK TO PK MAX @ DC TO 337.5 MHz
 VSWR:
 1.3:1 MAX @ DC TO 337.5 MHz
 REJECTION:
 50 dBc MIN @ 625 TO 4000 MHz
 POWER HANDLING:.....1 WATT
 IMPEDANCE:..... 50 OHMS NOM IN/OUT
 OPERATIONAL TEMP:..... -55 TO +125°C

COPY

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

ENGLISH / METRIC ENGLISH	CHECKED BY						
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125 OR BETTER REMOVE ALL BURRS	DRAWN BY PBF						
	ENGINEER KJR	II	10JAN08	KJR	DEV.	INI. ISS. PER 2811	
	REV	DATE	BY	DCN No.	REMARKS		

ENGLISH (INCHES) .XX ±.01 .XXX ±.005	METRIC (MM) .X ±.25 .XX ±.13	SCALE 4:1	APPLIC: LC LOWPASS FILTER
ANGLES ± 0° 30'	DATE 14JAN08	TITLE: 7LLC3-375/4000-SP	

MATERIAL: BRASS	DRAWING No. 0L0828	SHEET OF 1 1
FINISH: SILVER QQS 365		

NOTES:

FILTER MAY BE LABELED OR ETCHED.
 FILTER IS ROHS COMPLIANT.

