





2

1



ELECTRICAL CHARACTERISTICS	
CENTER FREQUENCY:	1730 MHz NOM.
BANDWIDTH:	50 MHz
PASSBAND FLATNESS:	0.5 dB / 25 MHz 1 dB / 50 MHz
GROUP DELAY:	4 NSEC PARABOLIC/50 MHz
REJECTION:	
	+/- 100 MHz: 60 dB
INSERTION LOSS:	6 dB MAX.
PASSBAND RETURN LOSS:	14 dB MIN.

**COPY**

NOTES:

1) THERE MUST BE A MINIMUM OF .050 AIR SPACE BETWEEN GROUND AND HIGH IMPEDANCE POINTS.

THIS MAY BE ACCOMPLISHED BY RAISING THE FILTER OR DRILLING OUT THE BOARD.

FILTER IS ROHS COMPLIANT.  
FILTER MAY BE LABELED OR ETCHED.

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

ENGLISH / METRIC ENGLISH	CHECKED BY						
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125/ OR BETTER REMOVE ALL BURRS	DRAWN BY EEF	II	23APR09	KJR	DEV.	INI. ISS. PER 3046	
	ENGINEER KJR	REV	DATE	BY	DCN No.	REMARKS	
ENGLISH (INCHES) .XX ±.02 .XXX ±.010	METRIC (MM) .X ±.5 .XX ±.25	SCALE 2:1	APPLIC: CERAMIC COAXIAL FILTER				
ANGLES ± 0° 30'	DATE 23APR09	TITLE: 8BCR6B-1730/C125-D					

	FINISH: JACKET: NICKEL/SILVER RESONATOR: SILVER	DRAWING No. 0L1014	SHEET OF 1 1
--	---	-----------------------	-----------------