



Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

NOTES:
 RECOMMENDED ATTACHMENT METHOD:
 SILVER EPOXY OR REFLOW NOT TO EXCEED AS INDICATED BELOW:

TEMP.(°C)	MAX.TIME(SEC)
215	90
230	60
245	30
260	15

FILTER IS ROHS COMPLIANT.
 FILTER MAY BE LABELED OR ETCHED.

ENGLISH / METRIC ENGLISH		CHECKED BY					
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125/0R BETTER REMOVE ALL BURRS		DRAWN BY PBF					
ENGLISH (INCHES) .XX ±.02 .XXX ±.010		METRIC (MM) .X ±.50 .XX ±.25		SCALE 2:1		APPLIC: CHIP AND WIRE FILTER	
ANGLES ± 0° 30'		DATE 08JUL10		TITLE: 5BLC1-422.5/180-LX		REMARKS INI. ISS. PER 3229	
FINISH: BOARD: NICKEL/GOLD JACKET: NICKEL/SILVER				DRAWING No. OL1107		SHEET OF 1 1	