



**COPY**

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

NOTES:

RECOMMENDED ATTACHMENT METHOD: SILVER EPOXY  
OR REFLOW NOT TO EXCEED AS INDICATED BELOW:

TEMP.(°C)	MAX.TIME(SEC)
215	90
230	60
245	30
260	15

FILTER IS ROHS COMPLIANT.  
FILTER MAY BE LABELED OR ETCHED.

ENGLISH / METRIC ENGLISH	CHECKED BY					
TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY					
MACHINED SURFACES TO BE 125 / OR BETTER	ENGINEER	II	29OCT12	KJR	DEV.	INI. ISS. PER 3596
REMOVE ALL BURRS	KJR	REV	DATE	BY	DCN No.	REMARKS
ENGLISH (INCHES)	SCALE	APPLIC: CERAMIC COAXIAL FILTER				
.XX $\pm$ .02 .XXX $\pm$ .010	4:1	TITLE: 8BCR3C-2000/90-L				
METRIC (MM)	DATE	DRAWING No.				
.X $\pm$ .50 .XX $\pm$ .25	05NOV12	SHEET OF 1 1				
ANGLES $\pm$ 0° 30'	FINISH:	BOARD: NICKEL/GOLD JACKET: NICKEL/SILVER RESONATOR: SILVER				
COMNAV ENGINEERING INC.		OL1322				