



ELECTRICAL CHARACTERISTICS	
CENTER FREQUENCY:	365 MHz NOM
3.0 dB BANDWIDTH:	68 MHz NOM
VSWR:	1.5:1 TYPICAL
INSERTION LOSS (350-380):	1.0 dB MAX
REJECTION:	
	30 dBc MIN/40 dBc GOAL @ 275 MHz
	30 dBc MIN/40 dBc GOAL @ 455 MHz

NOTES:

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

ENGLISH / METRIC CHECKED BY ENGLISH					
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125/ OR BETTER REMOVE ALL BURRS	DRAWN BY PBF	A	21FEB13	JSW	DEV. GEN. REV. PER 3632
	ENGINEER KJR	II	19DEC12	KJR	DEV. INI. ISS. PER 3607
	REV	DATE	BY	DCN No.	REMARKS

ENGLISH (INCHES) .XX ±.02 .XXX ±.01	METRIC (MM) .X ±.2 .XX ±.13	SCALE 2:1	APPLIC: CHIP AND WIRE FILTER
ANGLES ± 0° 30'	DATE 21FEB13	TITLE: 7BLC6-365/Z70-0	SHEET OF 1 1

	MATERIAL: ALUMINUM	DRAWING No. 0L1325
	FINISH: SILVER	