



ELECTRICAL CHARACTERISTICS

NOTCH 1575 MHz	
PASSBAND:	1565-1585 MHz
PASSBAND LOSS:	1.2 dB MAX
PASSBAND FLATNESS:	0.7 dB MAX
PASSBAND VSWR:	1.7:1
67 dB REJECTION:	1616-1626 MHz
BANDPASS 1621 MHz	
PASSBAND:	1616-1626 MHz
PASSBAND LOSS:	1.5 dB TYP./1.8 dB MAX
PASSBAND FLATNESS:	0.3 dB MAX
PASSBAND VSWR:	1.7:1
52 dBc REJECTION:	1565-1585 MHz
POWER HANDLING: 20 WATTS PK	

COPY

NOTES:
 FILTER MAY BE LABELED OR ETCHED.
 FILTER IS ROHS COMPLIANT.

ENGLISH / METRIC ENGLISH	CHECKED BY				
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125/ OR BETTER REMOVE ALL BURRS	DRAWN BY PBF	II	26JUL13	KJR	DEV.
	ENGINEER KJR	REV	DATE	BY	DCN No.
					REMARKS
ENGLISH (INCHES) .XX ±.02 .XXX ±.010	METRIC (MM) .X ±.25 .XX ±.13	SCALE 1:1	APPLIC: CERAMIC COAXIAL FILTER		
ANGLES ± 0° 30'	DATE 05AUG13	TITLE: 7DBNCR8B-1575/1621-0			

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

COMNAV ENGINEERING INC.

MATERIAL: COVER: ALUMINUM
 BASE: ALUMINUM

FINISH: COVER: SILVER PLATE
 BASE: SILVER PLATE

DRAWING No. 0L1358

SHEET OF 1 1