


ELECTRICAL CHARACTERISTICS

CENTER FREQUENCY: 156 MHz NOM
 PASSBAND: 88-233 MHz
 P.B. INSERTION LOSS: 2.0 dB MAX
 RETURN LOSS: 14 dB
 REJECTION:
 40 dBc MIN @ DC-45 MHz
 40 dBc MIN @ 470-4000 MHz
 SOURCE AND LOAD: 50 OHMS

NOTES:

RECOMMENDED FOOTPRINT: FP0169
 FILTER IS ROHS COMPLIANT.

COPY



Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

ENGLISH / METRIC ENGLISH	CHECKED BY				
TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY PBF				
MACHINED SURFACES TO BE 125 / OR BETTER REMOVE ALL BURRS	ENGINEER KJR	II	01OCT15	KJR	DEV. INI. ISS. PER 3956
ENGLISH (INCHES) .XX ±.02 .XXX ±.010	METRIC (MM) .X ±.25 .XX ±.13	SCALE 2:1	APPLIC: LC FILTER		
ANGLES ± 0° 30'	DATE 09OCT15	TITLE: 5BLC1-156/150-L			
COMNAV ENGINEERING INC.	FINISH: BOARD: NI/AU PLATED COPPER JACKET: NI/SILVER RESONATOR: SILVER		DRAWING No. OL1534		SHEET OF 1 1