


ELECTRICAL CHARACTERISTICS	
NOTCH 1575 MHz	
PASSBAND:	1565-1585 MHz
PASSBAND LOSS:	1.2 dB MAX
PASSBAND FLATNESS:	0.7 dB MAX
PASSBAND VSWR:	1.7:1
67 dB REJECTION:	1616-1626 MHz
BANDPASS 1621 MHz	
PASSBAND:	1616-1626 MHz
PASSBAND LOSS:	1.9 dB TYP./2.1 dB MAX
PASSBAND FLATNESS:	0.3 dB MAX
PASSBAND VSWR:	1.7:1
52 dBc REJECTION:	1565-1585 MHz
POWER HANDLING: 20 WATTS PK	

**COPY**



NOTES: FILTER MAY BE LABELED OR ETCHED. FILTER IS ROHS COMPLIANT.

ENGLISH / METRIC ENGLISH	CHECKED BY				
TOLERANCES UNLESS OTHERWISE SPECIFIED MACHINED SURFACES TO BE 125/ OR BETTER REMOVE ALL BURRS	DRAWN BY	A	14SEP16	KJR	DEV.
	ENGINEER	II	15MAR16	KJR	DEV.
ENGLISH (INCHES)	METRIC (MM)	SCALE	APPLIC: CERAMIC COAXIAL FILTER		
.XX ±.010 .XXX ±.005	.X ±.25 .XX ±.13	1:1	DATE	TITLE: 7DBNCR8BX-1575/1621-0	
ANGLES ± 0° 30'	14SEP16				
MATERIAL: COVER: ALUMINUM BASE: ALUMINUM			DRAWING No.		SHEET OF
FINISH: COVER: SILVER PLATE BASE: SILVER PLATE			0L1582		1 1

Confidential and Proprietary information of ComNav Engineering Inc. Do Not Duplicate or Use Without Permission. ComNav Engineering Inc. claims Copyright in this document as of the Creation, last revision, and last updated dates. All Rights Reserved.

